

CANADA SENSORS TECHNOLOGY INC.



Manufacturer of Advanced Technology Pressure & Level Transmitters

CRN Approval ISO 9001:2015



PRESSURE TRANSMITTER – PROCESS 3

General Purpose Service

Canada Sensors Technology Inc. offers an affordable solution with the Process 3 Pressure Transmitter without sacrificing quality or longevity of use.

FEATURES

- ✓ 4 – 20 mA Two Wire, Voltage, MODbus, CANbus, J1939, USB, Ethernet
- ✓ 0.25% BSL Accuracy
- ✓ Monolithic Block Glass Bonded One Piece Stainless Steel Machined Sensor
- ✓ No Welded Diaphragms, No Internal O-rings, No Silicone Oil Fill
- ✓ Single seal compliant to ANSI/ISA-12.27.01.2003
- ✓ Zero & Span Function
- ✓ >100 million Cycles
- ✓ Pressure Ranges from -30"Hg Vacuum to 10,000 PSI
- ✓ Heavy Duty 316SS Powder Coated Canister
- ✓ Temperature Compensated 0C to +50C
- ✓ Maximum Operating Temperature -40C to +95C
- ✓ Ingress Protection IP65
- ✓ Approved for General Purpose Use
- ✓ Multiple Electrical Connectors & Housings Available
- ✓ Multiple Process Connection Materials & Connection Threads Available
- ✓ Laser Engraved Product Information
- ✓ RoHS Compliant
- ✓ 2 Year Conditional Warranty (Serial Number Traceability)
- ✓ Unparalleled Value



Contact Us:

Canada Sensors Technology Inc.

10 – 328 Wale Road
Victoria, BC V9B 0J6
Canada
250-588-8085

sales@canadasensors.com
www.canadasensors.com

**Manufacturer of Advanced Technology
Level and Pressure Transmitters**



MISSION STATEMENT

Canada Sensors Technology Inc. strives to build a mutually positive and beneficial relationship with our customers, ensuring their long-term success, through the understanding of their needs and the needs of their customers.

We will listen to our customers and constantly improve our technologies as our customers' needs change with time.

Canada Sensors Technology Inc. is committed to providing the highest level of product quality and customer service.

Canada Sensors Technology Inc. operates a Quality Management System that ensures compliance with the requirements of ISO 9001:2015 and relevant legislation.

Technical Specifications - Process 3

Performance

Accuracy:	0.25% Full Scale Output
Stability:	< 0.1% Full Scale Output/Year
Temperature Range:	-40C to +95C
Temperature Accuracy:	1% Full Scale Output @ +50C
Pressure Cycles:	> 100 Million
Over Range Protection:	2 x Full Scale Output
Burst Pressure:	5 x Full Scale Output

NOTE: Over Range Protection and Burst Pressure shall be reduced to 1.5 x Full Scale Output for pressures exceeding 10,000 PSI due to thread limitations

Electrical Data

Excitation:	9-32 VDC (product accessories may alter excitation values)
Comms:	4-20 mA, 0-5 VDC or 0-10 VDC or Ratio Metric, RS485-Modbus, CANopen, J939, USB, Ethernet
Current Consumption:	5 mA
Zero Offset:	0.5% Full Scale Output
Span Tolerance:	0.5% Full Scale Output
Output Load:	9 Volts typical @ 24 VDC 750 OHMS

Pollution Degree 4

Installation Category I

Environmental Data

Temperature

Operating:	-40C to +95C (product accessories may alter temperature ratings)
Storage:	-55C to +125C

Thermal Limits

Compensated Range:	0 to +50C
Temp Comp Zero:	1% Full Scale Output @ +50C
Temp Comp Span:	1% Full Scale Output @ +50C

Physical Data


Sensor:	Monolithic Block: 17-4phSS, 316SS, Inconel-718, Titanium, Hastalloy-276
Vibration:	25gRMS from 20Hz to 2000Hz
Shock:	100g, half sine, 11mSec.
Sensor:	Silicone Oil Filled: 17-4phSS, 316SS, Inconel-718, Titanium, Hastalloy-276
Vibration:	25gRMS from 20Hz to 2000Hz
Shock:	100g, half sine, 11mSec.
NOTE: Silicone Oil Filled Sensors are a factory option for low pressure	
Process Connection:	1/4" MNPT; 1/4" FNPT; 1/2" MNPT; 1/2" FNPT; 1/4" SAE-Male; 1/4" SAE-Female; G-1/4"; G-1/2"; G-1/2" Flushmount, 1/4" MNPT Flushmount, 1/2" MNPT Flushmount
NOTE: ANSI Regulations dictate that NPT Thread should not to exceed 8,000 PSI @ +125C	
Electrical Connection:	316SS Thread-on 1/2" MNPT Solid Conduit Fitting or w/ Aluminum XP Heads; Big-DIN 43650A or w/LED Display; Bendix Twist 6 Pin (PTIH-10-6P); M12
NOTE: Big-DIN connection not approved for UV exposure	

NOTE: 316SS Wetted Parts are the minimum requirement for NACE compliance


Product Weights:

	OZ	LBS	KG
Process 3 w/ 316SS Thread-on 1/2" MNPT Solid Conduit Fitting (2 ft Lead)	20.5	1.3	0.58
Process 3 w/ Big-DIN (DIN 43650A 90 Degree Hirschmann) or Bendix Twist 6 Pin (PTIH-10-6P) or M12	11.5	0.7	0.33
Process 3 w/ Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting - Blank - No Window	55.5	3.5	1.57
Process 3 w/ Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting w/ 3 1/2 + Digits LCD Loop Powered Display	68.5	4.3	1.94
Process 3 w/ Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting w/ 5 Digits LCD Loop Powered Display	108.5	6.8	3.08
Process 3 w/ Big-DIN (DIN 43650A 90 Degree Hirschmann) w/ LED Display	19.5	1.2	0.55

Process Connections:



Electrical Connections:



Product Accessories

- Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting - Blank - No Window
- Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting w/ 3 1/2 + Digits LCD Loop Powered Display
- Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting w/ 5 Digits LCD Loop Powered Display



Two Wired Smart LED SQUARE Display Unit



Product Nomenclature

MODEL: Pressure Transmitter - Process 3

PN Example: A-B-C-D-E-F-G-H-I-J

03-01-03-01-025-02-01-12-02-02:

Process 3 Transmitter, 4-20 mA, Zero and Span, Gauge (PSIG), 0 - 1500 PSI, 1/4" FNPT, 17-4phSS Wetted Parts, 316SS Thread-on 1/2" MNPT Solid Conduit Fitting with 2 ft Lead Extension Wire, No Treatment, 0.25% Accuracy

		A	B	C	D	E	F	G	H	I	J
Model											
03	-	Process 3									
Output											
01	-	4-20 mA									
02	-	0-5 Volts									
03	-	0-10 Volts									
04	-	RS485 – Modbus									
05	-	CANopen									
06	-	J1939									
07	-	USB									
08	-	Ethernet									
Calibration Adjustment											
03	-	Zero and Span									
Pressure Reference											
01	-	Gauge (PSIG)									
02	-	Absolute (PSIA)									
03	-	Sealed Gauge									
Pressure Range											
001	-	-30"Hg Vac – 0 PSI									
002	-	-30"Hg Vac x 15 PSI									
003	-	-30"Hg Vac x 30 PSI									
004	-	-30"Hg Vac x 60 PSI									
005	-	-30"Hg Vac x 100 PSI									
006	-	-30"Hg Vac x 150 PSI									
007	-	-30"Hg Vac x 200 PSI									
008	-	-30"Hg Vac x 300 PSI									
009	-	-30"Hg Vac x 600 PSI									
010	-	0 – 2 PSI									
011	-	0 – 5 PSI									
012	-	0 – 10 PSI									
013	-	0 – 15 PSI									
014	-	0 – 30 PSI									
015	-	0 – 60 PSI									
016	-	0 – 100 PSI									
017	-	0 – 150 PSI									
018	-	0 – 200 PSI									
019	-	0 – 300 PSI									
020	-	0 – 400 PSI									
021	-	0 – 500 PSI									
022	-	0 – 600 PSI									
023	-	0 – 750 PSI									
024	-	0 – 1000 PSI									
025	-	0 – 1500 PSI									
026	-	0 – 2000 PSI									
027	-	0 – 3000 PSI									
028	-	0 – 4000 PSI									
029	-	0 – 5000 PSI									
030	-	0 – 6000 PSI									
031	-	0 – 7500 PSI									
032	-	0 – 10000 PSI									
Process Connection											
01	-	¼" MNPT									
02	-	¼" FNPT									
03	-	½" MNPT									
04	-	½" FNPT									
05	-	¼" SAE-Male									
06	-	¼" SAE-Female									
07	-	G-¼"									
08	-	G-1/2"									
10	-	G-1/2" Flushmount									
11	-	¼" MNPT Flushmount									
12	-	½" MNPT Flushmount									
Wetted Parts											
01	-	17-4phSS									
02	-	316SS									
03	-	Inconel-718									
04	-	Titanium									
05	-	Hastelloy-276									
Electrical Connection											
12	-	316SS Thread-on ½" MNPT Solid Conduit Fitting (2 ft Lead Extension Wire)									
13	-	316SS Thread-on ½" MNPT Solid Conduit Fitting (4 ft Lead Extension Wire)									
14	-	316SS Thread-on ½" MNPT Solid Conduit Fitting (6 ft Lead Extension Wire)									
15	-	316SS Thread-on ½" MNPT Solid Conduit Fitting (10 ft Lead Extension Wire)									
22	-	Big-DIN (DIN 43650A 90 Degree Hirschmann)									
31	-	Bendix Twist Connector 6 Pin (PTIH-10-6P)									
32	-	M12									
36	-	Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting - Blank - No Window									
39	-	Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting w/ 3 1/2 + Digits LCD Loop Powered Display									
42	-	Aluminum XP Head (1/2" FNPT x 3) - 316SS Thread-on 1/2" MNPT Solid Conduit Fitting w/ 5 Digits LCD Loop Powered Display									
91	-	Big-DIN (DIN 43650A 90 Degree Hirschmann) w/ LED Display									
Environmental Treatment											
02	-	No Treatment									
04	-	DLC (Diamond Like Coating)									
Accuracy											
02	-	0.25 %									

E: Alternate Pressure Range Units

kPa

kPa	001 - kPa	-	-100 x 0 kPa
kPa	002 - kPa	-	-100 x 100 kPa
kPa	003 - Kpa	-	-100 x 200 kPa
kPa	004 - Kpa	-	-100 x 400 kPa
kPa	005 - kPa	-	-100 x 700 kPa
kPa	006 - kPa	-	-100 x 1000 kPa
kPa	007 - kPa	-	-100 x 1400 kPa
kPa	008 - kPa	-	-100 x 2000 kPa
kPa	009 - kPa	-	-100 x 4000 kPa
kPa	010 - kPa	-	0 ~ 15 kPa
kPa	011 - kPa	-	0 ~ 35 kPa
kPa	012 - kPa	-	0 ~ 70 kPa
kPa	013 - kPa	-	0 ~ 100 kPa
kPa	014 - kPa	-	0 ~ 200 kPa
kPa	015 - kPa	-	0 ~ 400 kPa
kPa	016 - kPa	-	0 ~ 700 kPa
kPa	017 - kPa	-	0 ~ 1000 kPa
kPa	018 - kPa	-	0 ~ 1400 kPa
kPa	019 - kPa	-	0 ~ 2000 kPa
kPa	020 - kPa	-	0 ~ 2800 kPa
kPa	021 - kPa	-	0 ~ 3500 kPa
kPa	022 - kPa	-	0 ~ 4000 kPa
kPa	023 - kPa	-	0 ~ 5000 kPa
kPa	024 - kPa	-	0 ~ 7000 kPa
kPa	025 - kPa	-	0 ~ 10000 kPa
kPa	026 - kPa	-	0 ~ 14000 kPa
kPa	027 - kPa	-	0 ~ 20000 kPa
kPa	028 - kPa	-	0 ~ 28000 kPa
kPa	029 - kPa	-	0 ~ 35000 kPa
kPa	030 - kPa	-	0 ~ 40000 kPa
kPa	031 - kPa	-	0 ~ 50000 kPa
kPa	032 - kPa	-	0 ~ 70000 kPa

mBar

mBar	001 - mBar	-	-1000 x 0 mBar
mBar	002 - mBar	-	-1000 x 1000 mBar
mBar	003 - mBar	-	-1000 x 2000 mBar
mBar	004 - mBar	-	-1000 x 4000 mBar
mBar	005 - mBar	-	-1000 x 7000 mBar
mBar	006 - mBar	-	-1000 x 10000 mBar
mBar	007 - mBar	-	-1000 x 14000 mBar
mBar	008 - mBar	-	-1000 x 20000 mBar
mBar	009 - mBar	-	-1000 x 40000 mBar
mBar	010 - mBar	-	0 ~ 150 mBar
mBar	011 - mBar	-	0 ~ 350 mBar
mBar	012 - mBar	-	0 ~ 700 mBar
mBar	013 - mBar	-	0 ~ 1000 mBar
mBar	014 - mBar	-	0 ~ 2000 mBar
mBar	015 - mBar	-	0 ~ 4000 mBar
mBar	016 - mBar	-	0 ~ 7000 mBar
mBar	017 - mBar	-	0 ~ 10000 mBar
mBar	018 - mBar	-	0 ~ 14000 mBar
mBar	019 - mBar	-	0 ~ 20000 mBar
mBar	020 - mBar	-	0 ~ 28000 mBar
mBar	021 - mBar	-	0 ~ 35000 mBar
mBar	022 - mBar	-	0 ~ 40000 mBar
mBar	023 - mBar	-	0 ~ 50000 mBar
mBar	024 - mBar	-	0 ~ 70000 mBar
mBar	025 - mBar	-	0 ~ 100000 mBar
mBar	026 - mBar	-	0 ~ 140000 mBar
mBar	027 - mBar	-	0 ~ 200000 mBar
mBar	028 - mBar	-	0 ~ 275000 mBar
mBar	029 - mBar	-	0 ~ 350000 mBar
mBar	030 - mBar	-	0 ~ 400000 mBar
mBar	031 - mBar	-	0 ~ 500000 mBar
mBar	032 - mBar	-	0 ~ 700000 mBar

mm Hg		
mm Hg	001 - mm Hg	- -1500 x 0 mm Hg
mm Hg	002 - mm Hg	- -1500 x 800 mm Hg
mm Hg	003 - mm Hg	- -1500 x 1500 mm Hg
mm Hg	004 - mm Hg	- -1500 x 3000 mm Hg
mm Hg	005 - mm Hg	- -1500 x 5000 mm Hg
mm Hg	006 - mm Hg	- -1500 x 8000 mm Hg
mm Hg	007 - mm Hg	- -1500 x 10000 mm Hg
mm Hg	008 - mm Hg	- -1500 x 15000 mm Hg
mm Hg	009 - mm Hg	- -1500 x 30000 mm Hg
mm Hg	010 - mm Hg	- 0 - 100 mm Hg
mm Hg	011 - mm Hg	- 0 - 250 mm Hg
mm Hg	012 - mm Hg	- 0 - 500 mm Hg
mm Hg	013 - mm Hg	- 0 - 800 mm Hg
mm Hg	014 - mm Hg	- 0 - 1500 mm Hg
mm Hg	015 - mm Hg	- 0 - 3000 mm Hg
mm Hg	016 - mm Hg	- 0 - 5000 mm Hg
mm Hg	017 - mm Hg	- 0 - 8000 mm Hg
mm Hg	018 - mm Hg	- 0 - 10000 mm Hg
mm Hg	019 - mm Hg	- 0 - 15000 mm Hg
mm Hg	020 - mm Hg	- 0 - 20000 mm Hg
mm Hg	021 - mm Hg	- 0 - 25000 mm Hg
mm Hg	022 - mm Hg	- 0 - 30000 mm Hg
mm Hg	023 - mm Hg	- 0 - 40000 mm Hg
mm Hg	024 - mm Hg	- 0 - 50000 mm Hg
mm Hg	025 - mm Hg	- 0 - 80000 mm Hg
mm Hg	026 - mm Hg	- 0 - 100000 mm Hg
mm Hg	027 - mm Hg	- 0 - 150000 mm Hg
mm Hg	028 - mm Hg	- 0 - 200000 mm Hg
mm Hg	029 - mm Hg	- 0 - 250000 mm Hg
mm Hg	030 - mm Hg	- 0 - 300000 mm Hg
mm Hg	031 - mm Hg	- 0 - 400000 mm Hg
mm Hg	032 - mm Hg	- 0 - 500000 mm Hg

in H₂O (60° F)

in H ₂ O (60° F)	001 - in H ₂ O	- -400 x 0 in H ₂ O (60° F)
in H ₂ O (60° F)	002 - in H ₂ O	- -400 x 400 in H ₂ O (60° F)
in H ₂ O (60° F)	003 - in H ₂ O	- -400 x 800 in H ₂ O (60° F)
in H ₂ O (60° F)	004 - in H ₂ O	- -400 x 1500 in H ₂ O (60° F)
in H ₂ O (60° F)	005 - in H ₂ O	- -400 x 3000 in H ₂ O (60° F)
in H ₂ O (60° F)	006 - in H ₂ O	- -400 x 4000 in H ₂ O (60° F)
in H ₂ O (60° F)	007 - in H ₂ O	- -400 x 5000 in H ₂ O (60° F)
in H ₂ O (60° F)	008 - in H ₂ O	- -400 x 8000 in H ₂ O (60° F)
in H ₂ O (60° F)	009 - in H ₂ O	- -400 x 16500 in H ₂ O (60° F)
in H ₂ O (60° F)	010 - in H ₂ O	- 0 - 60 H ₂ O (60° F)
in H ₂ O (60° F)	011 - in H ₂ O	- 0 - 150 in H ₂ O (60° F)
in H ₂ O (60° F)	012 - in H ₂ O	- 0 - 300 in H ₂ O (60° F)
in H ₂ O (60° F)	013 - in H ₂ O	- 0 - 400 in H ₂ O (60° F)
in H ₂ O (60° F)	014 - in H ₂ O	- 0 - 800 in H ₂ O (60° F)
in H ₂ O (60° F)	015 - in H ₂ O	- 0 - 1500 in H ₂ O (60° F)
in H ₂ O (60° F)	016 - in H ₂ O	- 0 - 3000 in H ₂ O (60° F)
in H ₂ O (60° F)	017 - in H ₂ O	- 0 - 4000 in H ₂ O (60° F)
in H ₂ O (60° F)	018 - in H ₂ O	- 0 - 5000 in H ₂ O (60° F)
in H ₂ O (60° F)	019 - in H ₂ O	- 0 - 8000 in H ₂ O (60° F)
in H ₂ O (60° F)	020 - in H ₂ O	- 0 - 10000 in H ₂ O (60° F)
in H ₂ O (60° F)	021 - in H ₂ O	- 0 - 14000 in H ₂ O (60° F)
in H ₂ O (60° F)	022 - in H ₂ O	- 0 - 16000 in H ₂ O (60° F)
in H ₂ O (60° F)	023 - in H ₂ O	- 0 - 20000 in H ₂ O (60° F)
in H ₂ O (60° F)	024 - in H ₂ O	- 0 - 30000 in H ₂ O (60° F)
in H ₂ O (60° F)	025 - in H ₂ O	- 0 - 40000 in H ₂ O (60° F)
in H ₂ O (60° F)	026 - in H ₂ O	- 0 - 50000 in H ₂ O (60° F)
in H ₂ O (60° F)	027 - in H ₂ O	- 0 - 80000 in H ₂ O (60° F)
in H ₂ O (60° F)	028 - in H ₂ O	- 0 - 100000 in H ₂ O (60° F)
in H ₂ O (60° F)	029 - in H ₂ O	- 0 - 140000 in H ₂ O (60° F)
in H ₂ O (60° F)	030 - in H ₂ O	- 0 - 160000 in H ₂ O (60° F)
in H ₂ O (60° F)	031 - in H ₂ O	- 0 - 200000 in H ₂ O (60° F)
in H ₂ O (60° F)	032 - in H ₂ O	- 0 - 300000 in H ₂ O (60° F)

mm H₂O (4° C)

mm H ₂ O (4° C)	001 - mm H ₂ O	-	-10000 x 0 mm H ₂ O (4° C)
mm H ₂ O (4° C)	002 - mm H ₂ O	-	-10000 x 10000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	003 - mm H ₂ O	-	-10000 x 20000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	004 - mm H ₂ O	-	-10000 x 40000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	005 - mm H ₂ O	-	-10000 x 70000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	006 - mm H ₂ O	-	-10000 x 100000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	007 - mm H ₂ O	-	-10000 x 140000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	008 - mm H ₂ O	-	-10000 x 200000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	009 - mm H ₂ O	-	-10000 x 400000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	010 - mm H ₂ O	-	0 - 1400 mm H ₂ O (4° C)
mm H ₂ O (4° C)	011 - mm H ₂ O	-	0 - 3500 mm H ₂ O (4° C)
mm H ₂ O (4° C)	012 - mm H ₂ O	-	0 - 7000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	013 - mm H ₂ O	-	0 - 10000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	014 - mm H ₂ O	-	0 - 20000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	015 - mm H ₂ O	-	0 - 40000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	016 - mm H ₂ O	-	0 - 70000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	017 - mm H ₂ O	-	0 - 100000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	018 - mm H ₂ O	-	0 - 140000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	019 - mm H ₂ O	-	0 - 200000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	020 - mm H ₂ O	-	0 - 300000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	021 - mm H ₂ O	-	0 - 350000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	022 - mm H ₂ O	-	0 - 400000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	023 - mm H ₂ O	-	0 - 500000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	024 - mm H ₂ O	-	0 - 700000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	025 - mm H ₂ O	-	0 - 1000000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	026 - mm H ₂ O	-	0 - 1400000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	027 - mm H ₂ O	-	0 - 2000000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	028 - mm H ₂ O	-	0 - 3000000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	029 - mm H ₂ O	-	0 - 3500000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	030 - mm H ₂ O	-	0 - 4000000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	031 - mm H ₂ O	-	0 - 5000000 mm H ₂ O (4° C)
mm H ₂ O (4° C)	032 - mm H ₂ O	-	0 - 7000000 mm H ₂ O (4° C)

in Hg (32° F)

in Hg (32° F)	001 - in Hg	-	-30 x 0 in Hg (32° F)
in Hg (32° F)	002 - in Hg	-	-30 x 30 in Hg (32° F)
in Hg (32° F)	003 - in Hg	-	-30 x 6 0 in Hg (32° F)
in Hg (32° F)	004 - in Hg	-	-30 x 125 in Hg (32° F)
in Hg (32° F)	005 - in Hg	-	-30 x 200 in Hg (32° F)
in Hg (32° F)	006 - in Hg	-	-30 x 300 in Hg (32° F)
in Hg (32° F)	007 - in Hg	-	-30 x 400 in Hg (32° F)
in Hg (32° F)	008 - in Hg	-	-30 x 600 in Hg (32° F)
in Hg (32° F)	009 - in Hg	-	-30 x 1200 in Hg (32° F)
in Hg (32° F)	010 - in Hg	-	0 - 5 in Hg (32° F)
in Hg (32° F)	011 - in Hg	-	0 - 10 in Hg (32° F)
in Hg (32° F)	012 - in Hg	-	0 - 20 in Hg (32° F)
in Hg (32° F)	013 - in Hg	-	0 - 30 in Hg (32° F)
in Hg (32° F)	014 - in Hg	-	0 - 60 in Hg (32° F)
in Hg (32° F)	015 - in Hg	-	0 - 125 in Hg (32° F)
in Hg (32° F)	016 - in Hg	-	0 - 200 in Hg (32° F)
in Hg (32° F)	017 - in Hg	-	0 - 300 in Hg (32° F)
in Hg (32° F)	018 - in Hg	-	0 - 400 in Hg (32° F)
in Hg (32° F)	019 - in Hg	-	0 - 600 in Hg (32° F)
in Hg (32° F)	020 - in Hg	-	0 - 800 in Hg (32° F)
in Hg (32° F)	021 - in Hg	-	0 - 1000 in Hg (32° F)
in Hg (32° F)	022 - in Hg	-	0 - 1200 in Hg (32° F)
in Hg (32° F)	023 - in Hg	-	0 - 1500 in Hg (32° F)
in Hg (32° F)	024 - in Hg	-	0 - 2000 in Hg (32° F)
in Hg (32° F)	025 - in Hg	-	0 - 3000 in Hg (32° F)
in Hg (32° F)	026 - in Hg	-	0 - 4000 in Hg (32° F)
in Hg (32° F)	027 - in Hg	-	0 - 6000 in Hg (32° F)
in Hg (32° F)	028 - in Hg	-	0 - 8000 in Hg (32° F)
in Hg (32° F)	029 - in Hg	-	0 - 10000 in Hg (32° F)
in Hg (32° F)	030 - in Hg	-	0 - 12000 in Hg (32° F)
in Hg (32° F)	031 - in Hg	-	0 - 15000 in Hg (32° F)
in Hg (32° F)	032 - in Hg	-	0 - 20000 in Hg (32° F)

Bar			
Bar	001 - Bar	-	-1 x 0 Bar
Bar	002 - Bar	-	-1 x 1 Bar
Bar	003 - Bar	-	-1 x 2 Bar
Bar	004 - Bar	-	-1 x 4 Bar
Bar	005 - Bar	-	-1 x 7 Bar
Bar	006 - Bar	-	-1 x 10 Bar
Bar	007 - Bar	-	-1 x 14 Bar
Bar	008 - Bar	-	-1 x 20 Bar
Bar	009 - Bar	-	-1 x 40 Bar
Bar	010 - Bar	-	0 - 0.15 Bar
Bar	011 - Bar	-	0 - 0.35 Bar
Bar	012 - Bar	-	0 - 0.7 Bar
Bar	013 - Bar	-	0 - 1 Bar
Bar	014 - Bar	-	0 - 2 Bar
Bar	015 - Bar	-	0 - 4 Bar
Bar	016 - Bar	-	0 - 7 Bar
Bar	017 - Bar	-	0 - 10 Bar
Bar	018 - Bar	-	0 - 14 Bar
Bar	019 - Bar	-	0 - 20 Bar
Bar	020 - Bar	-	0 - 28 Bar
Bar	021 - Bar	-	0 - 35 Bar
Bar	022 - Bar	-	0 - 40 Bar
Bar	023 - Bar	-	0 - 50 Bar
Bar	024 - Bar	-	0 - 70 Bar
Bar	025 - Bar	-	0 - 100 Bar
Bar	026 - Bar	-	0 - 140 Bar
Bar	027 - Bar	-	0 - 200 Bar
Bar	028 - Bar	-	0 - 275 Bar
Bar	029 - Bar	-	0 - 350 Bar
Bar	030 - Bar	-	0 - 400 Bar
Bar	031 - Bar	-	0 - 500 Bar
Bar	032 - Bar	-	0 - 700 Bar

ata (kg/cm²)

ata (kg/cm ²)	001 - ata	-	-1 x 0 ata (kg/cm ²)
ata (kg/cm ²)	002 - ata	-	-1 x 1.0 ata (kg/cm ²)
ata (kg/cm ²)	003 - ata	-	-1 x 2.1 ata (kg/cm ²)
ata (kg/cm ²)	004 - ata	-	-1 x 4 ata (kg/cm ²)
ata (kg/cm ²)	005 - ata	-	-1 x 7 ata (kg/cm ²)
ata (kg/cm ²)	006 - ata	-	-1 x 10 ata (kg/cm ²)
ata (kg/cm ²)	007 - ata	-	-1 x 14 ata (kg/cm ²)
ata (kg/cm ²)	008 - ata	-	-1 x 21 ata (kg/cm ²)
ata (kg/cm ²)	009 - ata	-	-1 x 40 ata (kg/cm ²)
ata (kg/cm ²)	010 - ata	-	0 - 0.14 ata (kg/cm ²)
ata (kg/cm ²)	011 - ata	-	0 - 0.35 ata (kg/cm ²)
ata (kg/cm ²)	012 - ata	-	0 - 0.7 ata (kg/cm ²)
ata (kg/cm ²)	013 - ata	-	0 - 1 ata (kg/cm ²)
ata (kg/cm ²)	014 - ata	-	0 - 2.1 ata (kg/cm ²)
ata (kg/cm ²)	015 - ata	-	0 - 4 ata (kg/cm ²)
ata (kg/cm ²)	016 - ata	-	0 - 7 ata (kg/cm ²)
ata (kg/cm ²)	017 - ata	-	0 - 10 ata (kg/cm ²)
ata (kg/cm ²)	018 - ata	-	0 - 14 ata (kg/cm ²)
ata (kg/cm ²)	019 - ata	-	0 - 21 ata (kg/cm ²)
ata (kg/cm ²)	020 - ata	-	0 - 30 ata (kg/cm ²)
ata (kg/cm ²)	021 - ata	-	0 - 35 ata (kg/cm ²)
ata (kg/cm ²)	022 - ata	-	0 - 40 ata (kg/cm ²)
ata (kg/cm ²)	023 - ata	-	0 - 50 ata (kg/cm ²)
ata (kg/cm ²)	024 - ata	-	0 - 70 ata (kg/cm ²)
ata (kg/cm ²)	025 - ata	-	0 - 100 ata (kg/cm ²)
ata (kg/cm ²)	026 - ata	-	0 - 140 ata (kg/cm ²)
ata (kg/cm ²)	027 - ata	-	0 - 210 ata (kg/cm ²)
ata (kg/cm ²)	028 - ata	-	0 - 300 ata (kg/cm ²)
ata (kg/cm ²)	029 - ata	-	0 - 350 ata (kg/cm ²)
ata (kg/cm ²)	030 - ata	-	0 - 400 ata (kg/cm ²)
ata (kg/cm ²)	031 - ata	-	0 - 500 ata (kg/cm ²)
ata (kg/cm ²)	032 - ata	-	0 - 700 ata (kg/cm ²)