

CURRENT MEASUREMENT PROBES

MR SERIES AC/DC CURRENT PROBES

MODELS MR417 / 527

Hall Effect AC/DC current probes for Oscilloscopes and other instruments with waveform displays

SPECIFICATIONS

MODEL	MR417	MR527
ELECTRICAL		
Current Range	0.5 to 40A _{AC} , 60A _{DC} 0.5 to 400A _{AC} , 600A _{DC}	0.5 to 100A _{AC} , 150A _{DC} 0.5 to 1000A _{AC} , 1400A _{DC}
Output Signal	10mV/A, 1mV/A	
Frequency Range	DC to 30kHz (-3dB) (depending of current value)	
Phase Shift At 50/60Hz	≤2°@ 40A ≤1.5° @ 400A	≤2.2°@ 100A ≤1.5° @ 1000A
Load Impedance	>1MΩ and ≤100pF	
Overload	3000A _{DC} or 1000A _{AC} continuous for < 1kHz	
Zero Adjust	Automatic on both ranges	
Power Source	9V alkaline battery (NEDA 1060A, 6LR61) or 5V DC Micro-USB type B	
Battery Life	50H typical	
Low Battery Indication	Green LED blinking	
Overload Indication	Red LED on when measurement > than selected range	
Output Termination	6.5 ft (2m) coaxial cable with insulated BNC terminal	
MECHANICAL		
Maximum Conductor Size	Cables: (1) 0.18" (30mm) or (2) .94" (24mm) Bus Bar: (1) 1.97 x 0.39" (50 x 10mm) or (2) 1.23 x 0.39" (31.5 x 10mm) or (3) 0.98 x 0.31" (25 x 8mm)	Cables: (1) 1.5" (39mm) or (2) 1" (25.4mm) Bus Bar: (1) 1.97 x 0.49" (50 x 12.5mm) or (2) 0.98 x 0.2" (25 x 5mm); (1) 1.24 x 0.30" (31.5 x 10mm) or (3) 0.98 x 0.31" (25 x 8mm)
Dimensions (H x W x D)	8.82 x 3.82 x 1.73" (224 x 97 x 44mm)	9.31 x 3.82 x 1.73" (236.5 x 97 x 44mm)
Weight (with Battery)	0.98lbs (440g)	1.15lbs (520g)
ENVIRONMENTAL		
Operating Temperature	14° to +131°F (-10 to +55°C)	
Storage Temperature	-40° to +176°F (-40 to +80°C)	
Relative Humidity	Up to 85% @ 35°C	
SAFETY		
Ingress Protection	IP 40	
EMC	EN 61326-1	
Safety Rating	IEC 61010-1, EN 61010-2-32, Pollution Degree 2, 600V CAT III	



MR417

MR527



FEATURES

- The jaw shape enables users to clamp on to cables or small bus bars
- Powered by battery or standard external 5V power source via micro-USB connector
- Measures up to 1000A_{AC} and 1400A_{DC} (model dependent)
- Equipped with a Zero DC reset function
- Auto Power Off enable/disable function
- LED overload and low battery indicators
- Millivolt output compatible with most equipment and instruments
- Equipped with a coaxial lead and isolated BNC connectors for direct connection to an oscilloscope
- Battery life up to 50 hours
- Safety rating 600V CATIII



BNC Connector

WESCHLER INSTRUMENTS 800-903-9870 440-378-6580 www.weschler.com info@weschler.com

CATALOG NO.	DESCRIPTION
1200.84	AC/DC Current Probe Model MR417 (40A _{AC} , 60A _{DC} , 10mV/A & 400A _{AC} , 600A _{DC} , 1mV/A, BNC Output) Replaces MR461
1200.85	AC/DC Current Probe Model MR527 (100A _{AC} , 150A _{DC} , 10mV/A & 1000A _{AC} , 1400A _{DC} , 1mV/A, BNC Output) Replaces MR561



CURRENT MEASUREMENT PROBES

GENERAL PURPOSE PROBES SELECTION CHART

Series	Model	Ratio	Measurement Range		Output Signal		Phase Shift**	Maximum Conductor Size		Output Connection	Catalog No.	
			AC	DC	Current	Voltage		Ø Cable	Bus Bar			
	MN01	1000:1	2 to 150A		1mA/A*	—	N/A	0.39" (10mm)		Leads	2129.17	
	MN02		50mA to 100A 50mA to 90A			—					2129.20	
	MN03	—	2 to 100A		—	1mV/A					2129.18	
	MN05		5mA to 10A 1 to 100A		—	1mV/A 1mV/A					2129.19	
	MN103	—	1mA to 10A 1 to 100A		—	1mV/A 1mV/A	<10° <8° <3.5°	0.47" (12mm)			1031.02	
	MN106		1000:1		2 to 150A	1mA/A					—	1031.17
	MN114	—	1mA to 10A		—	100mV/A					2110.71	
	MN185	1000:1	50mA to 120A		1mA/A	—					Jacks	100.185
	MN213		1000:1	0.5 to 240A	—	1mA/A*	—	<2.5°	0.78" (19.8mm)	N/A	Leads	2115.75
	MN251	—				1mV/A	2115.77					
	MN253	—	0.1 to 24A 0.1 to 240A			—	10mV/A					2115.79
	MN255					—	100mV/A 10mV/A					2115.81
	MN291	—	0.5 to 240A	—	100mV _{DC} /A _{AC}	N/A	2115.84					
	MN307		10mA to 12A	—	100mV/A	2116.23						
	MN312	1000:1	0.1 to 200A		1mA/A*	—	<2.5°	Jacks			2116.24	
	MN313					—		Leads			2116.25	
	MN352	—	0.1 to 150A		—	10mV/A		Jacks			2116.26	
	MN353				—			2116.27				
	MN373	—	0.01 to 2.4A 0.1 to 200A		—	1000mV/A 10mV/A	<3°	2116.28				
	MN375				0.1 to 10A		—	100mV/A			<1.5°	2115.41
	MN379						5mA to 6A 0.1 to 120A					—
		SL206		10mA to 1.5A 50mA to 60A	10mA to 2A 50mA to 80A	—					1mV/mA _{AC} /DC 10mV/A _{AC} /DC	<1°
	MD301	1000:1	2 to 500A	—	—	1mV _{DC} /A _{AC}	N/A	1.18" (30mm) 2 x 500kcmil	2.48 x 0.20" (63 x 5mm)		1201.07	
	MD305		1 to 600A		1mA/A*	—	<1°				1201.36	

*Output Protection for open secondary

**Phase shift indicated at maximum rating

Note: Models MN103, MN106, MN114 & MN185 are not CE compliant. MN200 & MN300 series are UL approved except MN379.

Consult factory for NIST Calibration price.

WESCHLER INSTRUMENTS 800-903-9870 440-378-6580 www.weschler.com info@weschler.com

CURRENT MEASUREMENT PROBES

GENERAL PURPOSE PROBES SELECTION CHART

Series	Model	Ratio	Measurement Range		Output Signal		Phase Shift**	Maximum Conductor Size		Output Connection	Catalog No.		
			AC	DC	Current	Voltage		Ø Cable	Bus Bar				
	MR415	—	0.5 to 400A	0.5 to 600A	—	1mV/A	≤1.5°	1.18" (30mm)	2 bus bar 1.24 x 0.39" (31.5 x 10mm)	5 ft (1.5m) Lead	1200.80		
	MR416		0.5 to 40A 0.5 to 400A	0.5 to 60A 0.5 to 600A		10mV/A 1mV/A	≤2.2° ≤1.5°				1200.82		
	MR525		0.5 to 1000A	0.5 to 1400A		1mV/A	≤1.5°	1.53" (39mm)	2 bus bar 1.96 x 0.19" (50 x 5mm)		1200.81		
	MR526		0.5 to 100A 0.5 to 1000A	0.5 to 150A 0.5 to 1400A		10mV/A 1mV/A	≤2° ≤1.5°				1200.83		
	SR600	1000:1	0.1 to 1000A	—	1mA/A	—	<0.5°	2.05" (52mm)	1.96 x 0.19" (50 x 5mm)	Jacks	2113.42		
	SR601				1mA/A*						2113.43		
	SR604				1mA/A*					Leads	2113.44		
	SR634	250:5 500:5 1000:5	1 to 250A 1 to 500A 1 to 1000A		20mA/A 10mA/A 5mA/A*	<1°	Jacks			2113.48			
	SR651	—	0.1 to 1000A		—	1mV/A				<0.5°	2113.45		
	SR701	1000:1	1mA to 1000A		1mA/A*	—	<0.7°			Jacks	2116.29		
	SR704									2116.30			
	SR752	—	0.1 to 1000A		—	1mV/A	<1°			Leads	2116.32		
	SR759		1mA to 1A 10mA to 10A 0.1 to 100A 1 to 1000A			1000mV/A 100mV/A 10mV/A 1mV/A					2116.33		
	K100	—	0.1mA to 3A	0.05mA to ±4A	—	1mV/mA	N/A	0.18" (4.5 mm)	N/A	Plugs	1200.67		
	K110		0.1mA to 300mA	0.05mA to ±450mA		10mV/mA					2111.73		
	LM102	1000:1	50mA to 200A	—	1mA/A*	—	<3°	0.63" (16 mm)		Leads	2153.04		
	LM103	—	0.1 to 200A		—	1mV/A					2153.05		

*Output Protection for open secondary

**Phase shift indicated at maximum rating

Note: All SR probes listed on this chart are UL approved, however not all SR series probes are UL approved; please consult factory.
Consult factory for NIST Calibration price.



WESCHLER INSTRUMENTS 800-903-9870 440-378-6580 www.weschler.com info@weschler.com

OUTPUT TERMINATIONS

Lead with BNC

Insulated 6.5 ft (2m) coaxial cable with insulated BNC connector rated 600Vrms



Jacks

Two standard safety banana jacks (4mm)



Leads

Double/reinforced 5 ft (1.5m) leads with 4mm safety banana plug



Shrouded Banana Plugs

Two 4mm safety banana plugs; standard 3/4" (19mm) spacing



AMPFLEX® AND MINIFLEX® PROBES - SELECTION CHARTS

SERIES	MODEL	RATIO	MEASUREMENT RANGE	OUTPUT SIGNAL	MAXIMUM CONDUCTOR SIZE	CATALOG NO.
	MF 300-6-2-10-HF	—	30A / 300A	100mV/A, 10mV/A	1.77" (45mm)	2126.83
	MF 300-10-2-10-HF	—			2.95" (70mm)	2126.84
	MA114	—	3A / 30A / 300A / 3000A	1mV/mA, 100mV/A 10mV/A, 1mV/A	4" (101mm)	2153.41
	300-24-2-10	—	30A / 300A	100mV/A, 10mV/A	7.48" (190mm)	2112.88
	1000-24-1-1	—	1000A	1mV/A		2112.39
	1000-24-2-1	—	100A / 1000A	10mV/A, 1mV/A		2112.98
	1000-36-2-1	—			11" (290mm)	2113.00
	3000-24-1-1	—	3000A	1mV/A	7.48" (190mm)	2112.46
	3000-36-1-1	—			11" (290mm)	2112.48
	3000-24-2-1	—	300A / 3000A	10mV/A, 1mV/A	7.48" (190mm)	2113.05
	3000-36-2-1	—			11" (290mm)	2112.00
	3000-48-2-1	—			15" (390mm)	2112.01
	6000-36-2-0.1	—	600A / 6000A	1mV/A, 0.1mV/A	11" (290mm)	2113.21
	30000-24-2-0.1	—	3000A / 30,000A			2113.33
	24-3001	—	300A / 3000AAC	10mV/A, 1mV/A	7.48" (190mm)	2120.81

Consult factory for NIST Calibration price

OSCILLOSCOPE & BNC TERMINATED PROBES

MODEL	MEASUREMENT RANGE		OUTPUT SIGNAL	PHASE SHIFT*	MAXIMUM CONDUCTOR SIZE		OUTPUT CONNECTION
	AC	DC			Ø CABLE	BUS BAR	
 SL261	100mA to 10A 1 to 100A		100mV/A 10mV/A	<1.5°	0.46" (11.8mm)	N/A	6.6 ft (2m) Lead w/BNC
 MN261				<2.5°	0.78" (19.8mm)		
 SR661				<1°	2.05" (52mm)	1.96 x 0.19" (50 x 5mm)	
 MN251T MN379T	0.5 to 240A	—	1mV/A	<2.5°	0.78" (20mm)	0.78" (20mm)	10 ft (3m) Lead w/BNC
	0.005 to 6A		200mV/A	<4°			
	0.1 to 120A		10mV/A	<2.2°			
 MH60	0.5 to 100A	0.5 to 100A	10mV/A	<1°	1.02" (26mm)	N/A	6.6 ft (2m) Lead w/BNC
 MR417	0.5 to 40A 0.5 to 400A	0.5 to 60A 0.5 to 600A	10mV/A 1mV/A	≤2.2° ≤1.5°	1.18" (30mm)	2 bus bar 1.24 x 0.39" (31.5 x 10mm)	
 MR527	0.5 to 100A 0.5 to 1000A	0.5 to 150A 0.5 to 1400A		≤2.2° ≤1.5°	1.53" (39mm)	2 bus bar 1.96 x 0.19" (50 x 5mm)	

*Phase shift indicated at maximum rating. Note: All probes are rated 600V CAT III and CE compliant. Not all models are UL approved; please consult factory. Consult factory for NIST Calibration price.