

NEW 260-8P LED Lighted Particulate Resistant Analog VOM

Professionals have long recognized that a Simpson 260 analog meter is superior to the best DMM when monitoring fluctuating trends and rates. The NEW 260-8P “Lighted” features more attributes than its predecessors including a relay overload protection circuit that is resettable and also provides audible continuity checking.

Features & Benefits

- Lighted dial with gasketed cover (extreme particulate/moisture protection)
- Rechargeable (USB) lighting system
- LED and sound continuity indicator
- Battery charge indicator (on front)
- LED flashlight and protected charge port (on back)
- 36 measurement ranges – AC and DC voltage, current measurements, and resistance testing
- Safeguarded connections to prevent operator/tool contact with electrical connections
- Overload protection
- Easy to operate – two knobs control the selection of functions and ranges
- Rugged phenolic case with reinforced walls for maximum durability
- MADE IN THE USA



1 Year Warranty

Order Part #12402

Authorized Distributor:

WESCHLER INSTRUMENTS

phone: 800-903-9870 440-378-6580

fax: 800-903-9590 440-238-0660

www.weschler.com info@weschler.com

LED Lighted Dial

Gasketed
Lens Cover

LED Charge
Indicator

New Continuity
Indicator LED

Dial Light

Flashlight



LED Flashlight

USB Charge Port
and Protective Cap



Specifications

DC Voltage		
Ranges	Accuracy	Sensitivity
250mV, 1V, 2.5V, 10V, 25V, 50V, 250V, 500V, 1000V	2% of full scale	20KΩ per volt

AC Voltage		
Ranges	Accuracy	Sensitivity
2.5V, 10V, 25V, 50V, 250V, 500V, 1000V	3% of full scale	5KΩ per volt

Decibel	
Ranges	-20 to +50dB
Reference	0dB = 1mW into 600Ω

AC Current
Up to 250 AC amperes with AC Amp-Clamp Adapter Accessory 00545

DC Current		
Ranges	Accuracy	Voltage Drop: (Nominal)
50μA, 1mA, 10mA, 100mA, 500mA, 10A	1.5% of full scale 50μA 2.0% full scale, all others	250mV on 50μA/1mA; 255mV on 10mA/10A; 300mV on 100mA; 500mV on 500mA

Resistance		
Ranges	Accuracy	Maxium Indication
Rx1	2.5° of arc	0 - 2KΩ
Rx100	2.0° of arc	0 - 200KΩ
Rx10K		0 - 20MΩ

Batteries	1.5V D, 9V (Neda No.13F, 1604A)
Fuse	F1 1A, 250V, type 3AG, quick acting Littlefuse® Type 312001, F2 2A, 600V Littlefuse® Type BLS or 2A 600V, Bussman® Type BBS
Size	7"(H) x 5.5"(W) x 3.1" (D) (18 x 14 x 8 cm)
Weight	3 lbs. (1.4 Kg)
Rated Circuit-To-Ground Voltage	1000V AC/DC Max

Specifications subject to change without notice.